



Technical Specifications

| | |
|----------------------------------|--|
| Outer Dimensions WxHxD: | 305 x 350 x 211 mm |
| Weight: | 9,5 kg |
| Housing material: | sheet steel 12.03 |
| Colour: | powder coated, frameDB 502, doors similar RAL 9006 |
| Operating temperature: | +5...+50 °C |
| Relative humidity: | 5...95 %, non-condensing |
| Power requirement: | 110...240 VDC |
| Frequency Compartment ID: | 125 kHz |
| Backup Battery: | 12 VDC / 2.3 Ah |
| Digital Output: | 4x 30 VDC / 1 A for up to 16 alarms |
| Certifications: | CE |

Product Description

The proxSafe® Smart 4 is a small, compact key management system to store and manage up to four key positions. It offers enough space to manage four individual keys or four bunches of keys.

The Smart 4's focus is on simplicity; the user simply identifies on the Smart 4's integrated RFID reader (called "C-Connect Terminal") and the system automatically opens its door and releases only the keys the user is allowed to take.

The RFID-based keyTags allow the Smart 4 to automatically track all removals and returns and create electronic reports.

Features

- Zero-maintenance RFID technology
- Compact design
- Easy to use
- Emergency opening in case of power failure
- Standalone mode in case of network errors

Product family

proxSafe® is an intelligent management system for keys and equipment with comprehensive audit and reporting capabilities. Control access to individual items and restrict when they can be taken. Keys, radios, test equipment, tools, laptops and more can be managed efficiently with increased accountability. The powerful software Commander Connect allows easy configuration and control of users, access rights, time profiles and the creation of individual reports.

Notes

The Smart 4 is designed to work with the C-Connect terminal but can also work with all other terminals of the proxSafe® portfolio.



Find an overview of all associated proxSafe® products here: go.deister.com/kmen



For access to our specification libraries visit: go.deister.com/ab23

Dimensions

All dimensions in mm.

